

SAFETY DATA SHEET

1. Product and company (manufacturer) identification

Product:	Eslon Draintight 503B
Manufacturer:	Sekisui Chemical Co., Ltd.
Address:	Toranomon 2-10-4, Minato-ku, Tokyo 105-8566
Responsible section:	Urban Infrastructure & Environmental Products Company
Telephone:	+81-3-6748-6492
Urgent telephone:	+81-3-6748-6492
Fax:	+81-3-6748-6564
Urgent contact:	Same as above
Application & restriction	Bonding agent for polyvinyl chloride piping system for sewers. Other applications are prohibited.
Document number:	#503B

2. Hazards identification

GHS Classification		
Physicochemical hazards:	Explosives Flammable gases Aerosols Oxidizing gases Gases under pressure Flammable liquids Flammable solids Self-active chemicals Pyrophoric liquids Pyrophoric solids Self-heating chemicals Chemicals which, in contact with water, emit flammable gases Oxidizing liquids Oxidizing solids Organic peroxides Substances corrosive to metals Desensitized explosives	Not classified Not classified Not classified Not classified Not classified Not classified Not classified Not classified Not classified Not classified Classification not possible Not classified Not classified Not classified Not classified Classification not possible Not classified
Health hazards:	Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation: gas) Acute toxicity (inhalation: vapor) Acute toxicity (inhalation: dust and Skin corrosion/irritation Eye damage/irritation Respiratory sensitization Skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Aspiration hazard	Classification not possible Classification not possible Category 4 Not classified Classification not possible Classification not possible Category 1 Category 1 Classification not possible Category 1 Classification not possible Classification not possible Classification not possible Classification not possible Classification not possible Classification not possible Classification not possible
Environmental hazards:	Hazard to the aquatic environment (Acute hazard) Hazard to the aquatic environment (Long-term hazard) Hazard to the ozone layer	Classification not possible Classification not possible Classification not possible

Pictogram or symbol:



Signal word:

Hazard statement:

Precautionary statement:

Danger

(H312) Harmful in contact with skin.
(H314) Causes severe skin burns and eye damage.
(H317) May cause an allergic skin reaction.

Do not breathe dust/mist. (P260)
Avoid breathing dust/fume. (P261)
Wash hands and eyes thoroughly after handling. (P264)
Contaminated work clothing should not be allowed out of the workplace. (P272)
Wear protective gloves/protective clothing/eye protection/face protection. (P280)

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331)
IF ON SKIN: Wash with plenty of soap and water. (P302+P352)
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. (P303+P361+P353)
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. (P304+P340)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
Immediately call a POISON CENTER or doctor/physician. (P310)
Call a POISON CENTER or doctor/physician if you feel unwell. (P312)
Specific treatment (see label). (P321)
If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)
Take off contaminated clothing and wash it before reuse. (P362+P364)
Store locked up. (P405)
Dispose of contents/container in accordance with local/regional/national/international regulations. (P501)

3. Composition/information on ingredients

Nature of composition:

Chemical or common name:

Hazardous ingredients:

Mixture

Modified Polyamide amine and Polythiol

Tris(dimethylaminomethyl)phenol, Carbon black

Component	Content	CAS Number	Reference Number in Gazetted List in Japan	Others
Polyamide amine	20 — 30 %	Registered	Registered	
Polythiol	5 — 14 %	Registered	Registered	
Tris(dimethylaminomethyl)phenol	1 — 10 %	90-72-2	(3)-776	
Inorganic filling material	60 — 70 %	Registered	Registered	
Silica (Amorphous)	1 — 10 %	112926-00-8	(1)-548	
Carbon black	Less than 1 %	Registered	Registered	

※The content is listed as a range as it is confidential information.

4. First-aid measures

If vapor is inhaled:

If attached to skin:

If gets in eye:

If swallowed:

Special note to physician:

Take the affected person to a clean-air space and give him rest in a easy-breathing pose.
Seek physician's counsel as may be needed.

Immediately wipe off and wash the skin with plenty water and soap.
Take off the contaminated clothing's for cleaning.
Seek physicians counsel if he suffers from irritation or drowsiness.

Rinse cautiously with plenty water over 15 minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
Seek physician's counsel.

Immediately seek physician's counsel.
Rinse the mouth well and drink a lot of water to vomit.

No information

5. Fire-fighting measures

Extinguishing agents:

Prohibited extinguishing agent:

Specific hazards:

Proper extinguishing method:

Carbon dioxide, powder agent, foam agent

Water flux

Fire may cause to generate irritant, toxic or erosive gas.
Easily flammable. It will readily be ignited by heat, spark or flame.
Heating of container may cause explosion.
Easily inflammable liquid and vapor.

Remove surrounding combustibles and use extinguishing agents.
Use foam agent to choke a large scale fire.
Fight against fire standing to its windward as much as possible and wear Respirator if necessary.
The use of water can spread the fire and be dangerous.

6. Accidental release measures		
Health hazard precaution, protective wear and first-aid	Workers should use protective wears (See Chapter 8) to prevent contact with the spilt adhesive and inhalation of its vapor. Rope off the crowd from the leak spot. Prevent flow out to river, etc. so as not to badly affect the environment.	
Environmental hazard precaution:	For small scale leakage, use absorbent (sawdust, dirt, sand, waste rug) to remove most of the spill and collect in sealed containers.	
Recovery and neutralization:	For large scale leakage, build bank around the spill and lead the liquid to a safer place for recovery. Alternatively, absorb the spillage onto sand, rags, etc. and collect it in a sealed container.	
Prevention of secondary casualty:	Quickly remove all the combustibles from around the leak spot and provide extinguishers ready for use.	
7. Handling and storage precautions		
Handling	Technical measures:	Use protective wears if inhalation or skin contact is foreseen. No open flames.
	Local & total ventilation:	Handling work must be practiced in a room where local or total ventilation facility is functioning.
	Safe handling:	Ban of high temperature substance, sparking and fire at nearby points. Prohibition of eating, drinking and smoking while the product is used. Wash hands well after handling. Avoid contact of the product with eye, skin and clothing. Do not inhale vapor, mist and spray of the product. Handle it only after reading and understanding all the precautions. Use the product only in a well ventilated room or outdoors.
Storage	Storing conditions:	Store in a remote room from heat, sparks and naked flame. No smoking in the storage room. Store in a cool, ventilated room. Lock the storage room.
8. Exposure controls and personal protection		
Facility measures:	Local ventilation of closed work room or total proper ventilation to prevent vapor inhalation.	
Control concentration:	Not determined	
Permissible concentration (Exposure limit, Biological exposure guide line)		
	Japan society for occupational health. (2005 version)	Not determined
	ACGIH (2005 version) TLV-TWA	Not determined
Protective wears:		
	Respiratory protection:	Use aspirator with appropriate filter
	Hand protection:	Impermeable gloves
	Eye protection:	Glasses-type goggles with side plates.
	Skin and body protection:	Long-sleeve fatigue uniform
Hygienic measures:	Wash hands well after handling.	
9. Physical and chemical properties		
	Physical state	Viscous liquid
	Color	Gray
	Odor	Characteristic
	Melting point/Freezing point	No data available
	Boiling point or initial boiling point	No data available
	Flammability	No data available
	Lower and upper explosion limit/flammability limit	No data available
	Flash point	220°C
	Auto-ignition temperature	No data available
	Decomposition temperature	No data available
	pH	Not applicable
	Dynamic viscosity	Not applicable
	Solubility	Insoluble in water, soluble in common organic solvents
	n-octanol/water partition coefficient:	No data available
	Vapor pressure	Not applicable
	Density and/or relative density	1.6~1.9 (20°C)
	Relative vapor density	Heavier than air
	Particle characteristics	No data available

10. Stability and reactivity		
Stability:	Stable under normal conditions and handling.	
Chemical stability:	Stable under normal conditions and handling.	
Possibility of hazardous reaction:	Reacts with epoxy, isocyanate, strong acid.	
Prohibitive conditions:	Heat	
Prohibitive contact:	Epoxy, oxidizing agent.	
Hazardous decomposed substances:	Generates amine and organic matter by thermal decomposition.	
11. Hazard information		
Acute toxicity (oral)	Measurements of compound ATE mix=3583mg/kg The product, as the mixture, falls in Not classified	
Acute toxicity (dermal)	Measurements of compound ATE mix=1280mg/kg The product, as the mixture, falls in Category 4	
Skin corrosion/irritation	The product, as the mixture, falls in Category 2.	
Eye damage/irritation	The product, as the mixture, falls in Category 2B.	
Skin sensitization	The product, as the mixture, falls in Category 1.	
As a result of the Ministry of Health, Labor and Welfare’s toxicity study, mutagenicity tests using micro–organisms and chromosomal aberration tests using mammalian cultured cells showed mutagenicity exceeding the prescribed criteria and may cause health problems.		
12. Ecological information		
Ecotoxicity:	None known at present.	
Persistence/degradability:	None known at present.	
Ecological accumulative property:	None known at present.	
Mobility in soil:	None known at present.	
Hazard to the aquatic environment (Acute hazard):	Classification not possible	
Hazard to the aquatic environment (Long-term hazard):	Classification not possible	
Hazard to the ozone layer:	Does not contain any ingredients listed in the Annexes to the Montreal Protocol. Classification not possible.	
13. Notes on disposal		
Residual & waste:	In the disposal of residual and other wastes, observe the relevant laws /regulations and local government rules. Users of the product should contract with the local government or licensed 'Industrial Waste Processors' for disposal of waste. It is important to let the contractor know well of fire and health hazards of the product, prior to disposal.	
Contaminated containers & packages:	Clean the containers for reuse or dispose them properly in accordance with relevant regulations and local government rules. Completely empty containers prior to disposal.	
14. Transport information		
International rule		
UN number:	3259	
Proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. or POLYAMINES, SOLID, CORROSIVE, N.O.S.	
UN classification:	Class 8	
Packing group:	III	
Sea Pollution Prevention Act	Not applicable	
Domestic control:		
Guidance Number	154	
Onshore control info.	Observe the Fire Defense Law.	
Offshore control info.	Observe the Marine Vessel Safety Law.	
Air cargo control info.	Observe the Aviation Law.	
Special safety measure:	Observe the Fire Defense Law. On-board containers of hazardous material must be piled firmly and orderly to avoid falling, tumbling and breaking. Cargo of hazardous material must be transported in a way the containers or the material itself do not suffer severe friction and vibration. If possible cause of casualty, such as heavy leakage, is found during transportation, try to remedy the situation and notify the fact to the nearby fire department or the relevant bureau. The driver carrying hazardous material must hold Yellow Card. Do not load hazardous materials together with food and feedstuff.	

15. Regulatory information**Labor Safety and Hygiene Law:**

Hazardous materials to be notified to the authority (Chapter 57, Section 2)
 Carbon black
 Hazardous materials to be posted (Chapter 18 of Ordinance)
 Not applicable
 Mutagenicity chemical substance
 2nd class organic solvents (Solvent Addiction Prevention Rule, Clause 1.1.4)
 Not applicable
 Carcinogenicity of chemical substances
 (Ordinance on Industrial Safety and Health Chapter 34,Section 2-4)
 Not applicable
 Chemical substances that cause skin and other skin disorders
 (related to Article 22 of the Law).
 2,4,6-tris(dimethylaminomethyl)phenol
 Not applicable
 Not applicable
 Not applicable
 Not applicable

Fire Defense Law:**PRTR Law:****Poisonous & Deleterious Substance Control Law:****Sea Pollution Prevention Act****16. Other information****Literature:**

- 1) Chemicals Safety Data Sheet (MSDS) Part 1: Content and Order of Items
- 2) Guideline for MSDS Edition (Revised Edition) by Japan Chem. Ind. Assoc.
- 3) GHS Classification Database, Site of National Institute of Technology and Evaluation
- 4) Hazard Handbook of Chemicals by Japan Industrial Safety and Health Association
- 5) Hazard communication of chemicals based on GHS-Labelling and Safety Data Sheet (SDS) JIS Z 7253:2019

This data sheet is edited by referring to currently available information, however, it is not intended to guarantee the data values or the precision of contained information. The precautions mentioned above are for ordinary handling and use only therefore please handle with care by implementing appropriate safety measures for new application and usage.