SDS No.502B 1/5page

Implementation: Jun. 4, 2013 Issue Date: Jun. 1, 2024

SAFETY DATA SHEET

	pany (manufacturer) identificatio			
Product: Manufacturer:		Eslon Draintight 502B Sekisui Chemical Co., Ltd.		
	Address:	Toranomon 2–10–4, Minato–ku, Tok	wo 105-8566	
		Urban Infrastructure & Environment		
	Responsible section:	Pipe Systems Division	tal Froducts Company	
	Telephone:	+81-3-6748-6492		
	Urgent telephone:	+81-3-6748-6492		
	Fax:	+81-3-6748-6564		
	Urgent contact:	Same as above		
Application & re	estriction	Bonding agent for polyvinyl chloride piping system for sewers Other applications are prohibited. #502B		
Document numb	ber:			
Hazards identifica				
GHS Classificat		F 1 .		
	Physicochemical hazards:	Explosives	Not classified	
		Flammable gases	Not classified	
		Aerosols	Not classified	
		Oxidizing gases	Not classified	
		Gases under pressure	Not classified	
		Flammable liquids	Not classified	
		Flammable solids	Not classified	
		Self-active chemicals	Not classified	
		Pyrophoric liquids	Not classified Not classified	
		Pyrophoric solids		
		Self-heating chemicals	Classification not possil	
		Chemicals which, in contact with	Not classified	
		water, emit flammable gases	Not classified	
		Oxidizing liquids	Not classified	
		Oxidizing solids	Not classified	
		Organic peroxides Substances corrosive to metals	Classification not possil	
		Desensitized explosives	Not classified	
	Health hazards:	· · · ·		
	neaith nazaros:	Acute toxicity (oral)	Not classified	
		Acute toxicity (dermal)	Not classified	
		Acute toxicity (inhalation: gas)	Not classified	
		Acute toxicity (inhalation: vapor)	Classification not possil	
		Acute toxicity (inhalation: dust and mist)		
		Skin corrosion/irritation	Category 1	
		Eye damage/irritation	Category 1	
		Respiratory sensitization	Classification not possil	
		Skin sensitization	Category 1	
		Germ cell mutagenicity	Classification not possil	
		Carcinogenicity	Classification not possil	
		Reproductive toxicity	Classification not possil	
		Specific target organ toxicity	Classification not possil	
		(single exposure)	Closedification not not -	
		Specific target organ toxicity	Classification not possil	
		(repeated exposure)	Classification not nosal	
	Environmental hazards:	Aspiration hazard Hazard to the aquatic environment	Classification not possil Category 3	
	Environnental hazarus.	(Acute hazard)	Jalegury J	
		· ·	Classification not nosal	
		Hazard to the aquatic environment	Classification not possil	
		(Long-term hazard) Hazard to the ozone layer	Classification not possil	
	Pictogram or symbol:			



Signal word:

Danger

Hazard statement:	(H314) Causes severe skin burns and eye damage. (H317) May cause an allergic skin reaction. (H402) Harmful to aquatic life. May be harmful if swallowed.
Precautionary statement:	
•	Do not breathe dust/mist. (P260)
	Avoid breathing dust/fume. (P261)
	Wash hands and eyes thoroughly after handling. (P264)
	Contaminated work clothing should not be allowed out of the workplace. (P272)
	Avoid release to the environment. (P273)
	Wear protective gloves/protective clothing/eye protection/face protection.
	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331)
	IF ON SKIN: Wash with plenty of soap and water. (P302+P352)
	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. (P303+P361+P353)
	IF INHALED: Remove victim to fresh air and keep at rest in a position
	comfortable for breathing. (P304+P340)
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
	Immediately call a POISON CENTER or doctor/physician. (P310)
	Call a POISON CENTER or doctor/physician if you feel unwell. (P312)
	Specific treatment (see label). (P321)
	If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)
	Take off contaminated clothing and wash it before reuse. (P362+P364)
	Store locked up. (P405)
	Dispose of contents/container in accordance with
	local/regional/national/international regulations. (P501)

3. Composition/information on ingredients

Nature of composition: Mixture

Chemical or common name: Hazardous ingredients:

Modified Polyamide amine and Polythiol Tris(dimethylaminomethyl)phenol, Carbon black

Component	Content	CAS Number	Reference Number in Gazetted List in Japan	Others
Polyamide amine	10 - 20 %	Registered	Registered	
Polythiol	10 - 20 %	Registered	Registered	
Tris(dimethylaminomethyl)phenol	1 — 5 %	90-72-2	(3)-776	
Inorganic filling material	60 — 70 %	Registered	Registered	
Silica (Amorphous)	1 — 5 %	112926-00-8	(1)-548	
Carbon black	Less than 1 %	Registered	Registered	

XThe content is listed as a range as it is confidential information.

4. First-aid measures If vapor is inhaled:

If vapor is inhaled:	Take the affected person to a clean-air space and give him rest in a easy-
	breathing pose.
	Seek physician's counsel as may be needed.
If attached to skin:	Immediately wipe off and wash the skin with plenty water and soap.
	Take off the contaminated clothing's for cleaning.
	Seek physicians counsel if he suffers from irritation or drowsiness.
If gets in eye:	Rinse cautiously with plenty water over 15 minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	Seek physician's counsel.
If swallowed:	Immediately seek physician's counsel.
	Rinse the mouth well and drink a lot of water to vomit.
Special note to physician:	No information
5. Fire-fighting measures	
Extinguishing agents:	Carbon dioxide, powder agent, foam agent
Prohibited extinguishing agent:	Water flux
Specific hazards:	Fire may cause to generate irritant, toxic or erosive gas.
- F	Easily flammable. It will readily be ignited by heat, spark or flame.
	Heating of container may cause explosion.
	Easily inflammable liquid and vapor.
Proper extinguishing method:	Remove surrounding combustibles and use extinguishing agents.
	Use foam agent to choke a large scale fire.
	Fight against fire standing to its windward as much as possible and wear
	Respirator if necessary.
	The use of water can spread the fire and be dangerous.

6. Accidental release measures Health hazard precaution, protective wear and first- aid		Workers should use protective wears (See Chapter 8) to prevent contact with the spilt adhesive and inhalation of its vapor.
Environmental ha Recovery and ne	-	Rope off the crowd from the leak spot. Prevent flow out to river, etc. so as not to badly affect the environment. For small scale leakage, use absorbent (sawdust, dirt, sand, waste rug) to remove most of the spill and collect in sealed containers. For large scale leakage, build bank around the spill and lead the liquid to a safer place for recovery. Alternatively, absorb the spillage onto sand, rags, etc. and collect it in a sealed container.
Prevention of se	condary casualty:	Quickly remove all the combustibles from around the leak spot and provide extinguishers ready for use.
7. Handling and stora	ge precautions	
Handling	Technical measures:	Use protective wears if inhalation or skin contact is foreseen.
	Local & total ventilation:	No open flames. Handling work must be practiced in a room where local or total ventilation facility is functioning.
	Safe handling:	Ban of high temperature substance, sparking and fire at nearby points. Prohibition of eating, drinking and smoking while the product is used. Wash hands well after handling. Avoid contact of the product with eye, skin and clothing. Do not inhale vapor, mist and spray of the product. Handle it only after reading and understanding all the precautions. Use the product only in a well ventilated room or outdoors.
Storage	Otoving conditioner	
	Storing conditions:	Store in a remote room from heat, sparks and naked flame. No smoking in the storage room. Store in a cool, ventilated room. Lock the storage room.
8. Exposure controls and personal protection Facility measures:		Local ventilation of closed work room or total proper ventilation to prevent vapor inhalation.
Control concentration: Permissible concentration (Exposure limit, Biological exposure guide line)		Not determined
	Japan society for occupational health. (2005 version)	Not determined
	ACGIH (2005 version) TLV-TWA	Not determined
Protective wears		
Hygienic measure	Respiratory protection: Hand protection: Eye protection: Skin and body protection: es:	Use aspirator with appropriate filter Impermeable gloves Glasses-type goggles with side plates. Long-sleeve fatigue uniform Wash hands well after handling.
9. Physical and chem	ical properties	
	Physical state Color Odor Melting point/Freezing point	Viscous liquid Gray Characteristic No data available
	Boiling point or initial boiling point	No data available
	Flammability Lower and upper explosion limit/flammability limit	No data available No data available
	Flash point Auto-ignition temperature Decomposition temperature pH Dynamic viscosity Solubility n-octanol/water partition coefficient: Vapor pressure Density and/or relative density	220°C No data available No data available Not applicable Insoluble in water, soluble in common organic solvents No data available Not applicable $1.6 \sim 1.9 (20^{\circ}C)$
	Relative vapor density Particle characteristics	Heavier than air No data available

10. Stability and reactivity	
Stability:	Stable under normal conditions and handling.
Chemical stability:	Stable under normal conditions and handling.
Possibility of hazardous reaction:	Reacts with epoxy, isocyanate, strong acid.
Prohibitive conditions:	Heat
Prohibitive contact:	Epoxy, oxidizing agent.
Hazardous decomposed substances:	Generates amine and organic matter by thermal decomposition.
11. Hazard information	
Acute toxicity (oral)	Measurements of compound ATE mix=3200mg/kg
	The product, as the mixture, falls in Not classified
Acute toxicity (dermal)	Measurements of compound ATE mix=2381mg/kg
	The product, as the mixture, falls in Not classified
Skin corrosion/irritation	The product, as the mixture, falls in Category 1.
Eye damage/irritation	The product, as the mixture, falls in Category 1.

Skin sensitization

As a result of the Ministry of Health, Labor and Welfare's toxicity study, mutagenicity tests using micro-organisms and chromosomal aberration tests using mammalian cultured cells showed mutagenicity exceeding the prescribed criteria and may cause health problems.

The product, as the mixture, falls in Category 1.

Ec Pe Ec	ological information otoxicity: rsistence/degradability: ological accumulative property: bility in soil:	None known at present. None known at present. None known at present. None known at present.
Ha	zard to the aquatic environment (Acute hazard):	The product, as the mixture, falls in Category 3.
	zard to the aquatic environment (Long-term zard):	Classification not possible
Ha	zard to the ozone layer:	Does not contain any ingredients listed in the Annexes to the Montreal Protocol. Classification not possible.
13. Notes on disposal Residual & waste: Contaminated containers & packages:		In the disposal of residual and other wastes, observe the relevant laws /regulations and local government rules. Users of the product should contract with the local government or licensed 'Industrial Waste Processors' for disposal of waste.
		It is important to let the contractor know well of fire and health hazards of the product, prior to disposal. Clean the containers for reuse or dispose them properly in accordance with relevant regulations and local government rules. Completely empty containers prior to disposal.
14. Transport information International rule		
	UN number:	3259
	Proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. or POLYAMINES, SOLID, CORROSIVE, N.O.S.
	UN classification:	Class 8
	Packing group: Sea Pollution Prevention Act	III Not applicable
Do	mestic control:	
20	Guidance Number	154
	Onshore control info.	Observe the Fire Defense Law.
	Offshore control info.	Observe the Marine Vessel Safety Law. Observe the Aviation Law.
Sp	Air cargo control info. ecial safety measure:	Observe the Aviation Law. Observe the Fire Defense Law. On-board containers of hazardous material must be piled firmly and orderly to avoid falling, tumbling and breaking. Cargo of hazardous material must be transported in a way the containers or the material itself do not suffer severe friction and vibration. If possible cause of casualty, such as heavy leakage, is found during transportation, try to remedy the situation and notify the fact to the nearby fire department or the relevant bureau.

department or the relevant bureau. The driver carrying hazardous material must hold Yellow Card.

Do not load hazardous materials together with food and feedstuff.

15. Regulatory information	
Labor Safety and Hygiene	Law:

	Labor Safety and Hygiene Law: Fire Defense Law: PRTR Law: Poisonous & Deleterious Substance Control Law: Sea Pollution Prevention Act		 Hazardous materials to be notified to the authority (Chapter 57, Section 2) (Carbon black) Hazardous materials to be posted (Chapter 18 of Ordinance) (Not applicable) Mutagenicity chemical substance 2nd class organic solvents (Solvent Addiction Prevention Rule, Clause 1.1.4) (Not applicable) Carcinogenicity of chemical substances (Ordinance on Industrial Safety and Health Chapter 34,Section 2-4) (Not applicable) Chemical substances that cause skin and other skin disorders (related to Article 22 of the Law). 	
			(2,4,6-tris(dimethylaminomethyl)phenol) Not applicable Not applicable Not applicable Not applicable Not applicable	
16.	Other information			
10.	[Application notes].	This product has been developed and manufactured for construction and civil engineering applications. Do not use the product for applications other than those specified. If the product is to be used for medical or other special applications, please test and confirm the safety of the product in advance and use it at your own risk. Never use the product for implantation or injection into the body or for applications in which a part of the product may remain in the body.		
	Literature:	 Chemicals Safety Data Sheet (MSDS) Part 1: Content and Order of Items Guideline for MSDS Edition (Revised Edition) by Japan Chem. Ind. Assoc. GHS Classification Database, Site of National Institute of Technology and Evaluation Hazard Handbook of Chemicals by Japan Industrial Safety and Health Association Hazard communication of chemicals based on GHS-Labelling and Safety Data Sheet (SDS) JIS Z 7253:2019 		

This data sheet is edited by referring to currently available information, however, it is not intended to guarantee the data values or the precision of contained information. The precautions mentioned above are for ordinary handling and use only therefore please handle with care by implementing appropriate safety measures for new application and usage.